



UTAD3 ADT Tires

The UTECH UTAD3 is a premium E-3/L-3 pattern for loaders, articulated dump truck and graders. It is designed with aggressive non-directional tread pattern with big blocks and extra tough architecture, which delivers superior traction, great self-cleaning capability and lasting reliability.



Parts Details Of UTAD3 ADT Tires

Non-directional, multi-block tread engineered for superior traction and stability:

- Non-directional, multi-block tread engineered for superior traction and stability:
- The non-directional tread design with big blocks and open shoulder grooves delivers high fore, aft and lateral traction, and superior self-cleaning capability
- The ultra-wide tread design and enhanced radial construction design offer improved stability and high flotation.



Architecture enhanced with high tensile steel belt package and robust carcass for superior impact resistance and higher load capacity.

- High tensile steel belts package built in for better impact and puncture resistance.
- Robust carcass: new structure ply cord and lengthened ply cord wrapping-up.
- The bead bundle is designed in semicircle shape, which greatly increases the adhesion, making the bead part stronger and the structure more stable.

Tread base and sidewall thickened for better cut and puncture resistance:

- Super thick tread base is applied to increase the puncture resistance.
- The sidewall is thickened for better cut resistance and impact.
- Special cut resistance compound is used to increase the life cycle.

Specifications of UTAD3 ADT Tires

Size	Star Rating	TRA Code	Rim	Section width		Overall Diameter		Tread Depth		Load Index & Speed Symbol	Type
				in	mm	in	mm	32nds	mm		
17.5R25	★★	E3/L3	14.00/1.5	18	449	53	1347	34	27	167B/182A2	TL
20.5R25	★★	E3/L3	17.00/2.0	21	533	58	1482	39	31	177B/193A2	TL
23.5R25	★★	E3/L3	19.50/2.5	24	607	63	1602	52	41	185B/201A2	TL
26.5R25	★★	E3/L3	22.00/3.0	27	686	68	1735	48	38	193B/209A2	TL
29.5R25	★★	E3/L3	25.00/3.5	30	769	73	1860	53	42	200B/216A2	TL