



UTL3 Bulldozer Tires

The UTECH UTL3 is a loader and dozer tire pattern that is designed for long lasting performance in traction, stability, cut and impact resistance. It also offers low operational costs and excellent operator comfort safety.



Parts Details Of UTL3 Bulldozer Tires

Special sidewall design and thickened sidewall for better cut and puncture resistance:

- A special shoulder design applied to protect the sidewall from rocks and debris, and the sidewall is thickened to minimize damages from cuts.
- Super thick tread base is applied to increase the puncture resistance.



Non-directional, multi-block tread engineered for superior traction and stability

- The non-directional tread design with big blocks and open shoulder grooves delivers high fore, aft and lateral traction, and superior self-cleaning capability
- The ultra-wide tread design and enhanced radial construction design offer improved stability and high flotation.

More rubber to be worn and less heat generated:

- UTL3 is designed with 10% more rubber volume compared with competitors and wear resistant rubber compound is used to increase the wear life.
- Tread movement is limited so as to decrease the heat generation.

Improved impact resistance and extra load capacity enabled by reinforced tire architecture:

- The high tensile steel belt package built in for better impact and puncture resistance, and robust carcass is designed to deal with frequent twisting in application.

Specifications of UTL3 Bulldozer Tires

Size	Star Rating	TRA Code	Rim	Section width		Overall Diameter		Tread Depth		Load Index & Speed Symbol	Type
				in	mm	in	mm	32nds	mm		
17.5R25	★★	E3/L3	14.00/1.5	17.52	445	53.07	1348	35	28	167B/182A2	TL
20.5R25	★★	E3/L3	17.00/2.0	20.47	520	58.74	1492	35	28	177B/193A2	TL
23.5R25	★★	E3/L3	19.50/2.5	23.5	597	63.66	1617	40	31.5	185B/201A2	TL



Duratech Industrial (Jinan) Co., Ltd

26.5R25	★★	E3/L3	22.00/3.0	26.5	673	68.9	1750	45	36	193B/209A2	TL
29.5R25	★★	E3/L3	25.00/3.5	29.53	750	73.74	1873	54	43	200B/216A2	TL
29.5R29	★★	E3/L3	25.00/3.5	29.53	750	77.76	1975	54	43	202B/218A2	TL